

# BLAUTEK

## SOLID STATE RELAYS SINGLE AND THREE PHASE


3-32 Vdc Inputs

25A, 50A, 100A Available

24—660Vac Load Range

LED Indicator

Finger Safe Covers




CE

## Stocked Solid State Relays:

Part Number	Phases	Amperage Range	Control Voltage	Load Voltage	Frequency Range	On/Off Time	Status Indicator
<b>SSR-25A</b>	1	25A	3-32VDC	24-660VAC	47/63 HZ	100ms	<b>YES!</b>
<b>SSR-50A</b>	1	50A	3-32VDC	24-660VAC	47/63 HZ	100ms	<b>YES!</b>
<b>SSR-100A</b>	1	100A	3-32VDC	24-660VAC	47/63 HZ	100ms	<b>YES!</b>
<b>SSR-3-50A</b>	3	50A	3-32VDC	24-660VAC	47/63 HZ	100ms	<b>YES!</b>
<b>SSR-3-100A</b>	3	100A	3-32VDC	24-660VAC	47/63 HZ	100ms	<b>YES!</b>

## Specifications:

Control Voltage: 3-32 V dc  
Control Current: 6 ma-25 ma  
Load Voltage: 24-660 Vac  
Insulated Voltage:  $\geq$  2000 Vac 1 min.  
On/Off Time: 100 ms  
Frequency Range: 47 / 63 hz  
Status Inducator: Red LED  
Ambient Temp: -40 - 80 C  
Certifications: 

---

## Distributor:

---

**BLAUTEK**

3925 PEPPERVINE DR. ORLANDO, FL 32828  
TEL. 407-260-9796 FAX. 407-260-9795 WWW.BLAUTEK.COM